



IES ROAD REPORT
PHOTOMETRIC FILENAME : AX-100-30-5-D.IES

DESCRIPTIVE INFORMATION (From Photometric File)

IESNA:LM-63-2002
[TEST] 12474666.03
[TESTLAB] UL Verification Services Inc.
[ISSUE DATE] 8/29/2018
[MANUFAC] Express Imaging Systems LLC dba Evluma
[LUMCAT] AX-100-30-5-D (Scaled from AX-100-50-5-D)
[LUMINAIRE] Gray metal housing, white plastic reflector and dome glass
[MORE] lens
[LAMP] One (1) white LED with optic below
[BALLAST] Internal
[OTHER] This test was performed using the calibrated photodetector met
[MORE] hod of absolute photometry.

CHARACTERISTICS


IES Classification	Type V
Longitudinal Classification	Short
Lumens Per Lamp	N.A. (absolute)
Total Lamp Lumens	N.A. (absolute)
Luminaire Lumens	11953
Downward Total Efficiency	N.A. (absolute)
Total Luminaire Efficiency	N.A. (absolute)
Luminaire Efficacy Rating (LER)	120
Total Luminaire Watts	100
Ballast Factor	1.00
Upward Waste Light Ratio	0.01
Maximum Candela	4099.347
Maximum Candela Angle	0H 60V
Maximum Candela (<90 Degrees Vertical)	4099.347
Maximum Candela Angle (<90 Degrees Vertical)	0H 60V
Maximum Candela At 90 Degrees Vertical	80.736 (0.7% Luminaire Lumens)
Maximum Candela from 80 to <90 Degrees Vertical	354.682 (3.0% Luminaire Lumens)
Cutoff Classification (deprecated)	N.A. (absolute)

IES ROAD REPORT
PHOTOMETRIC FILENAME : AX-100-30-5-D.IES

LUMINAIRE CLASSIFICATION SYSTEM (LCS)

	Lumens	% Lamp	% Luminaire
FL - Front-Low (0-30)	532.8	N.A.	4.5
FM - Front-Medium (30-60)	3070.5	N.A.	25.7
FH - Front-High (60-80)	2242.9	N.A.	18.8
FVH - Front-Very High (80-90)	98.7	N.A.	0.8
BL - Back-Low (0-30)	532.8	N.A.	4.5
BM - Back-Medium (30-60)	3070.5	N.A.	25.7
BH - Back-High (60-80)	2242.9	N.A.	18.8
BVH - Back-Very High (80-90)	98.7	N.A.	0.8
UL - Uplight-Low (90-100)	48.2	N.A.	0.4
UH - Uplight-High (100-180)	15.3	N.A.	0.1
Total	11953.3	N.A.	100.0
BUG Rating	B3-U2-G2		


COEFFICIENTS OF UTILIZATION



FLUX DISTRIBUTION


	Lumens	Percent Of Luminaire
Downward Street Side	5944.9	49.7
Downward House Side	5944.9	49.7
Downward Total	11889.8	99.5
Upward Street Side	31.7	0.3
Upward House Side	31.7	0.3
Upward Total	63.4	0.5
Total Flux	11953.2	100.0

POLAR GRAPH




Maximum Candela = 4099.347 Located At Horizontal Angle = 0, Vertical Angle = 60
1 - Vertical Plane Through Horizontal Angles (0 - 180) (Through Max. Cd.)
2 - Horizontal Cone Through Vertical Angle (60) (Through Max. Cd.)

ISOFOOTCANDLE LINES OF HORIZONTAL ILLUMINANCE



LUMINAIRE CLASSIFICATION SYSTEM (LCS) GRAPH



Luminaire Lumens:
Front: Low=532.8, Medium=3070.5, High=2242.9, Very High=98.7
Back: Low=532.8, Medium=3070.5, High=2242.9, Very High=98.7
Uplight: Low=48.2, High=15.3

BUG Rating : B3-U2-G2