



UL LLC  
1075 W Lambert Rd Suite B  
Brea, CA 92821

## Outdoor Distribution Test Report

Relevant Standards  
IES LM-79-2008, ANSI C82.77-2002

Prepared For  
**Express Imaging Systems LLC dba Evluma**

Blake Coudriet  
3600 Lind Ave SW Suite 140  
Renton, WA 98057  
United States

Catalog Number  
**AX-30-27-5-D-BR**

Order Number  
12516546  
Test Number  
12516546.06

Test Date

2018-09-20

Prepared By

William Escobar, Technician

Approved By


Eric Gaudreau, Engineering Leader

The results contained in this report pertain only to the tested sample.  
This report shall not be reproduced, except in full, without written approval of Underwriters Laboratories.  
This report must not be used by the client to claim product certification, approval, or endorsement by  
NVLAP, NIST, or any agency of the Federal Government.



**Luminaire Description:** Gray metal housing, white plastic reflector and dome glass lens  
**Lamp:** One (1) white LED with optic below  
**Mounting:** Pole/Arm

### Luminaire



### Luminaire Characteristics

Luminous Diameter: 11.00 in.  
Luminous Height: 1.25 in.

### Summary of Results

Roadway Classification: Type V, Short  
Cutoff Classification: Cutoff  
BUG Rating: B2 U2 G1

### Test Conditions

Test Temperature: 24.8 °C  
Voltage: 120.1 VAC  
Current: 0.2638 A  
Power: 31.56 W  
Power Factor: 0.996  
Frequency: 60 Hz  
Current THD: 7.37 %

Tested in 30 planes left side, 30 planes right side, left and right averaged  
Vertical test increments are 2.5 degrees  
Test distance exceeds five times the greatest luminous opening of luminaire

Laboratory results may not be representative of field performance  
Ballast factors have not been applied



## Distribution - Goniophotometer


### Distribution Test Conditions

Temperature	Voltage	Current	Power	Power Factor	Frequency	Current THD
24.8 °C	120.1 VAC	0.2638 A	31.56 W	0.996	60 Hz	7.37 %

### Summary of Results


<b>IES Roadway Classification:</b>	Type V, Short	<b>Total Lumen Output:</b>	3985 Lumens
<b>Cutoff Classification</b>	Cutoff	<b>Luminaire Efficacy:</b>	126.3 lm/w
<b>BUG Rating:</b>	B2 U2 G1	<b>Maximum Candela:</b>	1366 Candela

### ISO FootCandle Plot at 20 Feet





**Maximum Plane and Cone Plots of Candela**



Vertical Plane Through

0 ° Lateral

Lateral Cone Through

57.5 ° Vertical

**Maximum Intensity (Candlepower):**


1366 Candela

**Zonal Lumen Summary**

Zone	Lumens	% of Luminaire	Zone	Lumens	% of Luminaire	Zone	Lumens	% of Luminaire
0-5	10.8	0.3%	60-65	617.9	15.5%	120-125	0.3	0.0%
5-10	30.3	0.8%	65-70	463.5	11.6%	125-130	0.2	0.0%
10-15	50.2	1.3%	70-75	245.0	6.1%	130-135	0.2	0.0%
15-20	70.1	1.8%	75-80	105.8	2.7%	135-140	0.1	0.0%
20-25	89.8	2.3%	80-85	45.4	1.1%	140-145	0.0	0.0%
25-30	109.8	2.8%	85-90	21.4	0.5%	145-150	0.0	0.0%
30-35	133.6	3.4%	90-95	10.4	0.3%	150-155	0.0	0.0%
35-40	174.1	4.4%	95-100	5.0	0.1%	155-160	0.0	0.0%
40-45	259.9	6.5%	100-105	2.1	0.1%	160-165	0.0	0.0%
45-50	389.1	9.8%	105-110	0.5	0.0%	165-170	0.0	0.0%
50-55	523.8	13.1%	110-115	0.3	0.0%	170-175	0.0	0.0%
55-60	624.7	15.7%	115-120	0.3	0.0%	175-180	0.0	0.0%



**IES "BUG" Rating**  
 (Back Light, Uplight, Glare)  
 Per IES TM-15-11



Luminaire Classification System (LCS)

LCS	Zone	Lumens	Luminaire %
FL	(0-30)	180.6	4.5%
FM	(30-60)	1052.6	26.4%
FH	(60-80)	716.1	18.0%
FVH	(80-90)	33.4	0.8%
BL	(0-30)	180.6	4.5%
BM	(30-60)	1052.6	26.4%
BH	(60-80)	716.1	18.0%
BVH	(80-90)	33.4	0.8%
UL	(90-100)	15.4	0.4%
UH	(100-180)	4.1	0.1%
Total		3984.8	100.0%
<b>BUG Rating</b>	<b>B2 U2 G1</b>		