



IES ROAD REPORT
PHOTOMETRIC FILENAME : AX-30-40-5-D.IES

DESCRIPTIVE INFORMATION (From Photometric File)

IESNA:LM-63-2002
[TEST] 12500748.03
[TESTLAB] UL Verification Services Inc.
[ISSUE DATE] 9/18/2018
[MANUFAC] Express Imaging Systems LLC dba Evluma
[LUMCAT] AX-30-40-5-D (Scaled from AX-30-50-5-D)
[LUMINAIRE] Gray metal housing, white plastic reflector and dome glass
[MORE] lens
[LAMP] One (1) white LED with optic below
[BALLAST] Internal
[OTHER] This test was performed using the calibrated photodetector met
[MORE] hod of absolute photometry.

CHARACTERISTICS


IES Classification	Type V
Longitudinal Classification	Short
Lumens Per Lamp	N.A. (absolute)
Total Lamp Lumens	N.A. (absolute)
Luminaire Lumens	4516
Downward Total Efficiency	N.A. (absolute)
Total Luminaire Efficiency	N.A. (absolute)
Luminaire Efficacy Rating (LER)	151
Total Luminaire Watts	30
Ballast Factor	1.00
Upward Waste Light Ratio	0.00
Maximum Candela	1595.683
Maximum Candela Angle	0H 60V
Maximum Candela (<90 Degrees Vertical)	1595.683
Maximum Candela Angle (<90 Degrees Vertical)	0H 60V
Maximum Candela At 90 Degrees Vertical	22.687 (0.5% Luminaire Lumens)
Maximum Candela from 80 to <90 Degrees Vertical	118.806 (2.6% Luminaire Lumens)
Cutoff Classification (deprecated)	N.A. (absolute)

IES ROAD REPORT
PHOTOMETRIC FILENAME : AX-30-40-5-D.IES

LUMINAIRE CLASSIFICATION SYSTEM (LCS)

	Lumens	% Lamp	% Luminaire
FL - Front-Low (0-30)	196.9	N.A.	4.4
FM - Front-Medium (30-60)	1150.6	N.A.	25.5
FH - Front-High (60-80)	870.8	N.A.	19.3
FVH - Front-Very High (80-90)	31.7	N.A.	0.7
BL - Back-Low (0-30)	196.9	N.A.	4.4
BM - Back-Medium (30-60)	1150.6	N.A.	25.5
BH - Back-High (60-80)	870.8	N.A.	19.3
BVH - Back-Very High (80-90)	31.7	N.A.	0.7
UL - Uplight-Low (90-100)	12.3	N.A.	0.3
UH - Uplight-High (100-180)	4.1	N.A.	0.1
Total	4516.4	N.A.	100.0
BUG Rating	B2-U2-G1		


COEFFICIENTS OF UTILIZATION



FLUX DISTRIBUTION


	Lumens	Percent Of Luminaire
Downward Street Side	2250.0	49.8
Downward House Side	2250.0	49.8
Downward Total	4499.8	99.6
Upward Street Side	8.2	0.2
Upward House Side	8.2	0.2
Upward Total	16.4	0.4
Total Flux	4516.2	100.0

POLAR GRAPH




Maximum Candela = 1595.683 Located At Horizontal Angle = 0, Vertical Angle = 60
1 - Vertical Plane Through Horizontal Angles (0 - 180) (Through Max. Cd.)
2 - Horizontal Cone Through Vertical Angle (60) (Through Max. Cd.)

ISOFOOTCANDLE LINES OF HORIZONTAL ILLUMINANCE



LUMINAIRE CLASSIFICATION SYSTEM (LCS) GRAPH



Luminaire Lumens:
Front: Low=196.9, Medium=1150.6, High=870.8, Very High=31.7
Back: Low=196.9, Medium=1150.6, High=870.8, Very High=31.7
Uplight: Low=12.3, High=4.1

BUG Rating : B2-U2-G1