



**IES ROAD REPORT**  
**PHOTOMETRIC FILENAME : AX-55-30-5-C.IES**

**DESCRIPTIVE INFORMATION (From Photometric File)**

IESNA:LM-63-2002  
[TEST] 12593999.07  
[TESTLAB] UL Verification Services Inc.  
[ISSUEDATE] 11/19/2018  
[MANUFAC] Express Imaging Systems LLC dba Evluma  
[LUMCAT] AX-55-30-5-C (Scaled from AX-70-50-5-C)  
[LUMINAIRE] Gray metal housing, white plastic reflector and cutoff gla  
[MORE] ss lens  
[LAMP] One (1) white LED with optic below  
[BALLAST] Internal  
[OTHER] This test was performed using the calibrated photodetector met  
[MORE] hod of absolute photometry.

**CHARACTERISTICS**


IES Classification	Type VS
Longitudinal Classification	Very Short
Lumens Per Lamp	N.A. (absolute)
Total Lamp Lumens	N.A. (absolute)
Luminaire Lumens	7472
Downward Total Efficiency	N.A. (absolute)
Total Luminaire Efficiency	N.A. (absolute)
Luminaire Efficacy Rating (LER)	136
Total Luminaire Watts	55
Ballast Factor	1.00
Upward Waste Light Ratio	0.00
Maximum Candela	2178.61
Maximum Candela Angle	155H 52.5V
Maximum Candela (<90 Degrees Vertical)	2178.61
Maximum Candela Angle (<90 Degrees Vertical)	155H 52.5V
Maximum Candela At 90 Degrees Vertical	0 (0.0% Luminaire Lumens)
Maximum Candela from 80 to <90 Degrees Vertical	297.021 (4.0% Luminaire Lumens)
Cutoff Classification (deprecated)	N.A. (absolute)

**IES ROAD REPORT**  
**PHOTOMETRIC FILENAME : AX-55-30-5-C.IES**

**LUMINAIRE CLASSIFICATION SYSTEM (LCS)**

	Lumens	% Lamp	% Luminaire
FL - Front-Low (0-30)	507.0	N.A.	6.8
FM - Front-Medium (30-60)	2199.7	N.A.	29.4
FH - Front-High (60-80)	970.9	N.A.	13.0
FVH - Front-Very High (80-90)	58.2	N.A.	0.8
BL - Back-Low (0-30)	507.0	N.A.	6.8
BM - Back-Medium (30-60)	2199.7	N.A.	29.4
BH - Back-High (60-80)	970.9	N.A.	13.0
BVH - Back-Very High (80-90)	58.2	N.A.	0.8
UL - Uplight-Low (90-100)	0.0	N.A.	0.0
UH - Uplight-High (100-180)	0.0	N.A.	0.0
Total	7471.6	N.A.	100.0
BUG Rating	B2-U0-G1		


**COEFFICIENTS OF UTILIZATION**



**FLUX DISTRIBUTION**


	Lumens	Percent Of Luminaire
Downward Street Side	3735.8	50.0
Downward House Side	3735.8	50.0
Downward Total	7471.6	100.0
Upward Street Side	0.0	0.0
Upward House Side	0.0	0.0
Upward Total	0.0	0.0
Total Flux	7471.6	100.0

POLAR GRAPH




Maximum Candela = 2178.61 Located At Horizontal Angle = 155, Vertical Angle = 52.5  
# 1 - Vertical Plane Through Horizontal Angles (155 - 335) (Through Max. Cd.)  
# 2 - Horizontal Cone Through Vertical Angle (52.5) (Through Max. Cd.)

ISOFOOTCANDLE LINES OF HORIZONTAL ILLUMINANCE



LUMINAIRE CLASSIFICATION SYSTEM (LCS) GRAPH



Luminaire Lumens:  
Front: Low=507.0, Medium=2199.7, High=970.9, Very High=58.2  
Back: Low=507.0, Medium=2199.7, High=970.9, Very High=58.2  
Uplight: Low=0.0, High=0.0

BUG Rating : B2-U0-G1