

AreaMax Conversion Chart



The updated 2019 AreaMax delivers more lumens for less energy.
Evluma recommends replacing AM Models with the following AX Models.

AM Model (2016)				AX Model (2019)					
Base Cat. No.	Watts	Lumens	lm/W	Base Cat. No.	Watts	Lumens	fewer	more	lm/W
							watts	lumens	
AM-40-3K-V-C	40	3900	100	AX-30-30-5-C	30	4300	-25%	+400	145
AM-40-3K-V-D	40	4000	103	AX-30-30-5-D	30	4400	-25%	+400	147
AM-40-4K-V-C	40	4000	107	AX-30-40-5-C	30	4400	-25%	+400	149
AM-40-4K-V-D	40	4100	109	AX-30-40-5-D	30	4500	-25%	+400	151
AM-40-5K-V-C	40	4000	108	AX-30-50-5-C	30	4500	-25%	+500	151
AM-40-5K-V-D	40	4100	111	AX-30-50-5-D	30	4500	-25%	+400	153
AM-55-3K-V-C	55	5000	97	AX-40-30-5-C	40	5600	-27%	+600	142
AM-55-3K-V-D	55	5100	100	AX-40-30-5-D	40	5700	-27%	+600	144
AM-55-4K-V-C	55	5300	99	AX-40-40-5-C	40	5800	-27%	+500	147
AM-55-4K-V-D	55	5300	104	AX-40-40-5-D	40	5900	-27%	+600	149
AM-55-5K-V-C	55	5300	104	AX-40-50-5-C	40	5900	-27%	+600	148
AM-55-5K-V-D	55	5600	108	AX-40-50-5-D	40	6000	-27%	+400	150
AM-70-3K-V-C	70	6800	98	AX-55-30-5-C	55	7400	-21%	+600	136
AM-70-3K-V-D	70	7000	104	AX-55-30-5-D	55	7500	-21%	+500	137
AM-70-4K-V-C	70	7000	106	AX-55-40-5-C	55	7700	-21%	+700	140
AM-70-4K-V-D	70	7500	109	AX-55-40-5-D	55	7800	-21%	+300	142
AM-70-5K-V-C	70	7600	108	AX-55-50-5-C	55	7700	-21%	+100	141
AM-70-5K-V-D	70	7700	113	AX-55-50-5-D	55	7800	-21%	+100	143
AM-40-3K-3-C	40	4000	101	AX-30-30-3-C	30	4400	-25%	+400	148
AM-40-3K-3-D	40	4200	105	AX-30-30-3-D	30	4500	-25%	+300	150
AM-40-4K-3-C	40	4200	105	AX-30-40-3-C	30	4500	-25%	+300	152
AM-40-4K-3-D	40	4300	110	AX-30-40-3-D	30	4600	-25%	+300	154
AM-40-5K-3-C	40	4300	109	AX-30-50-3-C	30	4600	-25%	+300	154
AM-40-5K-3-D	40	4500	114	AX-30-50-3-D	30	4600	-25%	+100	156
AM-70-3K-3-C	70	6100	88	AX-55-30-3-C	55	7500	-21%	+1400	138
AM-70-3K-3-D	70	6500	91	AX-55-30-3-D	55	7700	-21%	+1200	140
AM-70-4K-3-C	70	6600	92	AX-55-40-3-C	55	7800	-21%	+1200	143
AM-70-4K-3-D	70	6900	96	AX-55-40-3-D	55	7900	-21%	+1000	145
AM-70-5K-3-C	70	6700	92	AX-55-50-3-C	55	7900	-21%	+1200	144
AM-70-5K-3-D	70	7100	99	AX-55-50-3-D	55	8000	-21%	+900	146

AM compatible with light shield AMAX-LTS

AX compatible with light shield AX-LTS4

Application requirements previously met by AM models may be met by installing the corresponding AX model in the chart above.
For a limited time, AM models remain available, however, the AX models listed above provide greater efficacy and lumen output.

The following ConnectLED versions are compatible with AX:

iOS – 1.1.0 (2/5/2018), Android – 2.3.0 (3/2/2018), Windows - 2.0.1 (2/5/2018) and up.

If you need assistance updating the ConnectLED app please contact: SwSupport@evluma.com