

evluma



OLS-2-AA2



OLS-1-A1

solutions for post top lighting

**Build-Your-Own Acorn**

featuring OmniMax™



OLS-1-B1

# Build-Your-Own Acorn

## Extraordinary Quality, Everyday Affordability, Time-Saving Versatility

Build-Your-Own Acorn delivers a complete, customizable architectural lighting solution featuring the OmniMax, Evluma's patented, screw-in LED retrofit as the light source. Avoid complicated kits, difficult mountings, elaborate wiring and large minimum requirements. Select only what you need to complete your project on-time and on budget.

Please see product documentation for OmniMax, globes (OLS), fitter (CF8), Photocontrol Failsafe and the ConnectLED app for a complete technical capabilities profile.

### Materials

**Globes are offered in three material types.**

**LD Acrylic:** Evluma's recommendation for best-in-class, visually-pleasing lighting. Optical transmission >90%. Impact resistant.

**Clear Acrylic:** Stays sparkling after prolonged use. Resistant to weathering and aging, including damage from UV, also impact resistant. Optical transmission up to 92%.

**Clear Polycarbonate:** Recommended for extreme environments with a high impact resistance even at subzero temperatures. UV stabilized. Optical transmission up to 88%.

### Uplight Blocker

Uplight blocker decreases upward light 30-40% and increases downlight by 20-25%.

#### OLS-2-AA2

Choose Type III or Type V, add uplight blocker or finial.



#### OLS-2-AA1

Choose Type III or Type V, add uplight blocker or finial.

### The OmniMax™

This long-life light source was designed to emulate, yet outperform, legacy HID bulbs. OmniMax delivers beautiful light in your choice of six color temperatures.




#### Premium/Standard:

OmniMax Premium includes Evluma's innovative solutions for smart lighting: Photocontrol Failsafe & compatibility with ConnectLED. Is beautiful light all you need? Order OmniMax Standard.

#### ConnectLED™:


Wirelessly control OmniMax Premium via an iOS or Android device using this helpful Bluetooth app.



#### Photocontrol Failsafe™:

Say goodnight to "dayburners," and never roll another truck to replace a failed photocontrol.

### Fitter CF8



Capital fitter is cast aluminum with a ceramic mogul socket.

Paint is a durable Tiger Drylac powder coat with excellent weather and UV resistance.

Order with or without a photocontrol, in black, green or bronze. Fits 3" & 4" poles.

### Optional Photocontrol

Evluma has specified a utility-grade, fail-on photocontrol with an IR-Filtered phototransistor for the CF8-PC. This 120-277VAC ANSI C136.24 photocontrol draws less than 0.4W and is IP65.

### Warranty

The base, capital fitter CF8, has a 5-year warranty on the finish. Evluma warrants that polycarbonate or acrylic products shall be free from workmanship defects for five years from date of purchase. Acrylic globes are warranted for 5 years against yellowing. Polycarbonate products are not warranted for yellowing over time.

The OmniMax and all electronics, including the capital's optional photocontrol are warranted for 10 years.


#### OLS-4-BB2

Choose Type III or Type V, black or green, photocontrol optional.



#### OLS-4-BB1

Choose black or green. photocontrol optional.



## How to Order

Order 1+2+3 (OmniMax + Base + Globe) + Accessory  
or Order 1+4 (OmniMax + Architectural Assy) + Accessory  
See next page for individual catalog numbers and options.

### Example 1+2+3

OMNI-70-3K-MO  
CF8-NC-BL  
OLS-1-A1-LD-8F

### Accessory

OM-LTS-KIT  
OLS-1-FINIAL

### Example 1+4

OMNI-70-3K-MO-STD  
OLS-4-BB1-AC-8F-PC-BL

### Accessory

OM-LTS-KIT


### OM Accessory Order Separately

OmniMax Shields

OM-LTS-KIT

OM-LTS-B1

OM-LTS-U1



### Globe Accessory Order Separately

Product

OLS-1-FINIAL

OLS-1-A1 & B1  
OLS-2-AA1



Product

OLS-2-BLOCKER

OLS-2-AA1 Only



# Build-Your-Own Acorn Ordering

For detailed product information please see the additional documentation for OmniMax, globes (OLS), and fitter (CF8).

**1** **OmniMax** OMNI-70 - \_ \_ - MO - \_ \_ \_

Product	CCT	Base	Option
<b>OMNI-40</b> = 40W OmniMax	<b>2K</b> = 2000K <b>22</b> = 2200K	<b>MO</b> = Mogul	<b>STD</b> = standard
<b>OMNI-70</b> = 70W OmniMax	<b>27</b> = 2700K <b>3K</b> = 3000K		
<b>OMNI-100</b> = 100W OmniMax	<b>4K</b> = 4000K <b>5K</b> = 5000K		



Standard ships without Bluetooth or Photocontrol Failsafe built-in.

**2** **Base** CF8 - \_ \_ - \_ \_

Product	Photocontrol	Color
<b>CF8</b> = 8" Fitter	<b>PC</b> = photocontrol <b>NC</b> = no photocontrol	<b>BL</b> = black <b>GN</b> = green <b>BZ</b> = bronze



**3** **Globe 1** OLS-1- \_ \_ - \_ \_ - 8F

Product	Style (Size)	Material	Neck Size
<b>OLS-1</b> Globe	<b>A1</b> = 26.81h x 16.6w <b>A2</b> = 25.19h x 16.5w <b>A3</b> = 21.18h x 14w	<b>LD</b> = LD Acrylic <b>AC</b> = acrylic clear <b>PC</b> = polycarbonate clear	<b>8F</b> = 8 inch

**Globe 2-AA1** OLS-2-AA1-AC-8F - \_ \_

Product	Distribution
<b>OLS-2-AA1-AC-8F</b> = Globe Style 2-AA1 Clear Acrylic, 8" Neck 27.19h x 15.9w	<b>3</b> = type III <b>5</b> = type V

**Globe-2-AA2** OLS-2-AA2-AC-8F- \_ \_ - \_ \_

Product	Distribution	Finial
<b>OLS-2-AA2-AC-8F</b> = Globe Style 2-AA2 Clear Acrylic, 8" Neck 23.16h x 15.9w	<b>3</b> = type III <b>5</b> = type V	<b>BF</b> = black finial <b>RF</b> = raw finial <b>NF</b> = no finial




**Globe 1-B1** OLS-1-B1 - \_ \_ - 8F

Product	Material	Neck Size
<b>OLS-1-B1</b> = Globe Style B1 23h x 15.13w	<b>LD</b> = LD Acrylic <b>AC</b> = acrylic clear <b>PC</b> = polycarbonate clear	<b>8F</b> = 8 inch

**Globe-2-AA3** OLS-2-AA3-AC-8F- \_ \_ - \_ \_

Product	Distribution	Finial
<b>OLS-2-AA3-AC-8F</b> = Globe Style 2-AA3 Clear Acrylic, 8" Neck w/ Uplight Blocker 23.16h x 15.9w	<b>3</b> = type III <b>5</b> = type V	<b>BF</b> = black finial <b>RF</b> = raw finial <b>NF</b> = no finial




**4** **Assy-4-BB1** OLS-4-BB1-AC-8F- \_ \_ - \_ \_

Product	Photocontrol	Color
<b>OLS-4-BB1-AC-8F</b> = Globe Style 4-BB1 Acrylic Globe. fits 3" & 4" poles 38h x 17.25w includes finial	<b>PC</b> = photocontrol <b>NC</b> = no photocontrol	<b>BL</b> = black <b>GN</b> = green



**Assy-4-BB2** OLS-4-BB2-AC-8F- \_ \_ - \_ \_

Product	Photocontrol	Distribution	Color
<b>OLS-4-BB2-AC-8F</b> = Globe Style 4-BB2 Acrylic Globe. fits 3" & 4" poles 36h x 16w includes finial	<b>PC</b> = photocontrol <b>NC</b> = no photocontrol	<b>3</b> = type 3 <b>5</b> = type 5	<b>BL</b> = black <b>GN</b> = green



Evluma makes one thing: Utility-grade outdoor LED lighting solutions

From heat management, to light quality, to integrated controls, we've been solving the biggest challenges in LED for over 2 decades. We help cities, municipalities and utility providers evolve their lighting infrastructure to meet needs of tomorrow.



846 Industry Drive  
Seattle, WA 98188  
425-336-5800 [www.evluma.com](http://www.evluma.com)