

Omni**Max**®

The LED Replacement lamp that doesn't compromise



Unique Design

Beautiful Light

Easy Installation





Omni**Max**®

Rethinking LED in Every Direction

OmniMax is a compact, omni-directional LED replacement lamp for Acorn, Post Top, Pendant and other decorative and architectural outdoor light fixtures. OmniMax enables you to seamlessly transition to LED technology while maintaining the light quality of your existing fixture. Like all Evluma products, OmniMax is engineered to last and backed by a 10 year comprehensive warranty.

The Best Overall Value in LED Replacements


Cost	Efficiency	Reliability		
Less than ½ the	Less than ⅓ the	10 year warranty		
price of many	energy of a 100W			
OEM retrofits	HPS (vs 40W OM)			

Product Configurations

- + 40W, 70W & 100W
- + Replaces 70-175W HID Bulbs
- + 5000K, 4000K, 3000K, 2700K, 2200K & 2000K CCT
- + E26 or E39 base







Compact Size

OmniMax emulates the HID bulbs it replaces. It installs easily in any fixture and uses the luminaire's optics as they were designed.



Omnidirectional **Light Engine**

The 96 radially mounted LEDs at the OmniMax's burn center provide light that is consistent, adjustable, and pleasant.



Photocontrol Failsafe™

Say goodnight to "dayburners," and never roll another truck to replace a failed photocontrol.



ConnectLED™

Walk-by programming via iOS or Android device using secure, BLE technology.



Features

- 1 Brushless fan with > 90,000 hr life
- ② Thermal protection circuitry
- 3 Molded silicone, matte-finish optics
- 4 20kV/10kA surge protection
- 5 96 radially mounted LEDs
- ⑥ Photocontrol Failsafe™
- ① E26 or E39 Base



Fits Any Luminaire







Acorn



Ordering Information Sample Number: OMNI-70-3K-MO

Product Family	Watts (nom)	ССТ	Base	Option	CRI	Source Lumens	LED mA	Lm/W	
40W LED (Recommended to replace up to 100W HPS / 150W MH)									
OMNI	40	2K = 2000K	ME = Medium	STD = Standard		>3800		>93	
		22 = 2200K				>4200		>97	
DLC		27 = 2700K		Standard ships without Bluetooth or Photocontrol Failsafe built-in.	>80	>5300	60 mA	>135	
		3K = 3000K	MO = Mogul			>5400		>138	
		4K = 4000K				>5600		>143	
	ти	5K = 5000K				>5700		>145	
70W LED	(Recommend	ded to replace up	to 150W HPS / 175W	/ MH)					
	70	2K = 2000K	ME = Medium	STD = Standard Standard ships without Bluetooth or Photocontrol Failsafe built-in.	>80	>5900	105 mA	>87	
		22 = 2200K				>6600		>92	
	_	27 = 2700K	MO = Mogul			>8500		>122	
	•	3K = 3000K				>8700		>125	
		4K = 4000K				>9000		>130	
ЦБПА	Tu.	5K = 5000K				>9100		>132	
100W LED	(Recomme	nded to replace up	to 150W HPS / 175	W MH)	ı				
OMNI	100	2K = 2000K	ME = Medium	STD = Standard	>80	>7675	138 mA	>75	
		22 = 2200K	MO = Mogul	Standard ships without Bluetooth or Photocontrol Failsafe built-in.		>8125		>80	
		27 = 2700K				>10650		>108	
		3K = 3000K				>11225		>110	
		4K = 4000K				>11650		>115	
		5K = 5000K				>11800		>115	











Only select MO base models are qualfied by The DesignLights Consortium www.designlights.org/search/

Technical Specs

Certification Data

UL 1598/8750 & UL1598C MET ANSI C136.31 3G Level 2 Vibration Bridge/Overpass

Electrical

120-277 VAC 60hz

Evluma Proprietary Class II Driver 20kV/10kA Category High C surge protection IEEE/ ANSI C62.41.2 - 2002 100W tested to IEEE/ANSI C136.2:2018

Power Factor >99% at 120 VAC THD <19% at 120 VAC Power Factor >95% at 277 VAC THD <11% at 277 VAC

Lumen Maintenance

L70 (10,000) > 60,000 LM at 10,000 hours = 97% LM at 100,000 hours = 80% L70 (TM-21) > 100,000

-40°C Min Ambient Temp (Outside Fixture) 40°C Max Ambient Temp (Outside Fixture)

Evluma makes one thing: Utility-grade outdoor LED lighting solutions

From heat management, to light quality, to integrated controls, we've been solving the biggest challenges in LED for over 2 decades. We help cities, municipalities and utility providers evolve their lighting infrastructure to meet needs of tomorrow.



3600 Lind Avenue SW Suite 140 Renton WA 98057 425-336-5800 www.evluma.com