

## Outdoor Distribution Test Report

**Catalog Number**

RoadMax RX2, 70W, 3000K, Type III, Diffused Lens  
RX2 070 E3 T3 G1

**Test Number**

Scaled from RX2-140E3T3G1-14703860.07

**Test Date**

3/10/2023

The results contained in this report pertain only to this IES file.

RoadMax RX2, 70W, 3000K, Type III, Diffused Lens  
RX2 070 E3 T3 G1

**Input**

Number of Lamps	1
Lumens per Lamp	N/A lm
Total Input Lumens	N/A lm
Input Watts	70 W

**Output**

Total Output Lumens	8960 lm
Efficiency	N/A %
Efficacy	128 lm/W


**Luminous Dimensions**

0° - 180° Size	1.06 ft
90° - 270° Size	1.31 ft
Height	0 ft

**Roadway Summary**

Total Luminaire Optical Efficiency	N/A %
IESNA lateral classification	Type III
IESNA vertical classification	Undefined (Very Short)
Cutoff classification	Semicutoff
IESNA TM-15-11 BUG Rating	B2 U0 G3
Maximum Candela	3114.8 at 0° horizontal, 17.5° vertical.
Street side total	70.35 %
House side total	29.65 %

### Candela Polar Plot




### Zonal Lumen Summary

Zone	Lumens	% Fixture	Zone	Lumens	% Fixture
0° - 10°	229.28	2.56%	90° - 100°	0.00	0.00%
10° - 20°	644.86	7.20%	100° - 110°	0.00	0.00%
20° - 30°	987.23	11.02%	100° - 120°	0.00	0.00%
30° - 40°	1241.12	13.85%	120° - 130°	0.00	0.00%
40° - 50°	1441.57	16.09%	130° - 140°	0.00	0.00%
50° - 60°	1571.05	17.53%	140° - 150°	0.00	0.00%
60° - 70°	1484.99	16.57%	150° - 160°	0.00	0.00%
70° - 80°	1044.75	11.66%	160° - 170°	0.00	0.00%
80° - 90°	315.15	3.52%	170° - 180°	0.00	0.00%
0° - 90°	8960.00	100.00%	0° - 180°	8960.00	100.00%
0° - 75°	8196.02	91.47%	75° - 90°	763.98	8.53%

**Average Luminare Luminance [cd/m<sup>2</sup>]**


	0.00°	45.00°	90.00°
0.00°	18489	18489	18489
45.00°	25462	28454	30066
55.00°	24876	34435	37702
65.00°	20800	46084	46882
75.00°	15209	44341	60559
85.00°	15609	37915	29928

### Roadway Coefficients of Utilization




Mounting Heights	1	2	3	4	5	6	7	8	9	10
House Side CU	0.24	0.28	0.29	0.29	0.29	0.29	0.29	0.29	0.29	0.29
Street Side CU	0.48	0.63	0.67	0.69	0.69	0.69	0.70	0.70	0.70	0.70

### IES TM-15-11 BUG Ratings



### Peak Intensity



### Iso-Illuminance Plot

