

Outdoor Distribution Test Report

Catalog Number

RoadMax RX2, 120W, 3000K, Type III, No Lens
RX2 120 E3 T3 G0

Test Number

Scaled from RX2-140E3T3G0-14703860.08A

Test Date

3/22/2023

The results contained in this report pertain only to this IES file.

RoadMax RX2, 120W, 3000K, Type III, No Lens
RX2 120 E3 T3 G0

Input

Number of Lamps	1
Lumens per Lamp	N/A lm
Total Input Lumens	N/A lm
Input Watts	120 W

Output

Total Output Lumens	16089.99 lm
Efficiency	N/A %
Efficacy	134.08 lm/W


Luminous Dimensions

0° - 180° Size	1.06 ft
90° - 270° Size	1.31 ft
Height	0 ft

Roadway Summary

Total Luminaire Optical Efficiency	N/A %
IESNA lateral classification	Type III
IESNA vertical classification	Short
Cutoff classification	Noncutoff
IESNA TM-15-11 BUG Rating	B3 U0 G3
Maximum Candela	7496.1 at 77.5° horizontal, 65° vertical.
Street side total	73.63 %
House side total	26.37 %

Candela Polar Plot




Zonal Lumen Summary

Zone	Lumens	% Fixture	Zone	Lumens	% Fixture
0° - 10°	390.68	2.43%	90° - 100°	0.00	0.00%
10° - 20°	1083.15	6.73%	100° - 110°	0.00	0.00%
20° - 30°	1613.01	10.02%	100° - 120°	0.00	0.00%
30° - 40°	1980.80	12.31%	120° - 130°	0.00	0.00%
40° - 50°	2272.00	14.12%	130° - 140°	0.00	0.00%
50° - 60°	3015.24	18.74%	140° - 150°	0.00	0.00%
60° - 70°	3374.57	20.97%	150° - 160°	0.00	0.00%
70° - 80°	1945.39	12.09%	160° - 170°	0.00	0.00%
80° - 90°	415.15	2.58%	170° - 180°	0.00	0.00%
0° - 90°	16089.99	100.00%	0° - 180°	16089.99	100.00%
0° - 75°	14902.84	92.62%	75° - 90°	1187.15	7.38%

Average Luminare Luminance [cd/m²]


	0.00°	45.00°	90.00°
0.00°	30992	30992	30992
45.00°	42198	41686	52007
55.00°	55476	54973	79091
65.00°	27318	126123	124343
75.00°	8063	71344	148408
85.00°	6457	21239	75457

Roadway Coefficients of Utilization




Mounting Heights	1	2	3	4	5	6	7	8	9	10
House Side CU	0.22	0.25	0.26	0.26	0.26	0.26	0.26	0.26	0.26	0.26
Street Side CU	0.49	0.68	0.72	0.73	0.73	0.73	0.73	0.73	0.73	0.73

IES TM-15-11 BUG Ratings



Peak Intensity



Iso-Illuminance Plot

