

## Outdoor Distribution Test Report

**Catalog Number**

RoadMax RX2, 100W, 2700K, Type III, No Lens  
RX2 100 E7 T3 G0

**Test Number**

Scaled from RX2-140E3T3G0-14703860.08A

**Test Date**

3/22/2023

The results contained in this report pertain only to this IES file.

RoadMax RX2, 100W, 2700K, Type III, No Lens  
RX2 100 E7 T3 G0

**Input**

Number of Lamps	1
Lumens per Lamp	N/A lm
Total Input Lumens	N/A lm
Input Watts	100 W

**Output**

Total Output Lumens	12320 lm
Efficiency	N/A %
Efficacy	123.2 lm/W


**Luminous Dimensions**

0° - 180° Size	1.06 ft
90° - 270° Size	1.31 ft
Height	0 ft

**Roadway Summary**

Total Luminaire Optical Efficiency	N/A %
IESNA lateral classification	Type III
IESNA vertical classification	Short
Cutoff classification	Noncutoff
IESNA TM-15-11 BUG Rating	B2 U0 G3
Maximum Candela	5739.7 at 77.5° horizontal, 65° vertical.
Street side total	73.63 %
House side total	26.37 %

### Candela Polar Plot




### Zonal Lumen Summary

Zone	Lumens	% Fixture	Zone	Lumens	% Fixture
0° - 10°	299.14	2.43%	90° - 100°	0.00	0.00%
10° - 20°	829.36	6.73%	100° - 110°	0.00	0.00%
20° - 30°	1235.07	10.02%	100° - 120°	0.00	0.00%
30° - 40°	1516.68	12.31%	120° - 130°	0.00	0.00%
40° - 50°	1739.65	14.12%	130° - 140°	0.00	0.00%
50° - 60°	2308.75	18.74%	140° - 150°	0.00	0.00%
60° - 70°	2583.89	20.97%	150° - 160°	0.00	0.00%
70° - 80°	1489.57	12.09%	160° - 170°	0.00	0.00%
80° - 90°	317.88	2.58%	170° - 180°	0.00	0.00%
0° - 90°	12320.00	100.00%	0° - 180°	12320.00	100.00%
0° - 75°	11411.00	92.62%	75° - 90°	909.00	7.38%

**Average Luminare Luminance [cd/m<sup>2</sup>]**


	0.00°	45.00°	90.00°
0.00°	23730	23730	23730
45.00°	32311	31919	39821
55.00°	42478	42092	60559
65.00°	20917	96572	95209
75.00°	6176	54626	113636
85.00°	4945	16267	57775

### Roadway Coefficients of Utilization




Mounting Heights	1	2	3	4	5	6	7	8	9	10
House Side CU	0.22	0.25	0.26	0.26	0.26	0.26	0.26	0.26	0.26	0.26
Street Side CU	0.49	0.68	0.72	0.73	0.73	0.73	0.73	0.73	0.73	0.73

### IES TM-15-11 BUG Ratings



### Peak Intensity



### Iso-Illuminance Plot

