

Outdoor Distribution Test Report

Catalog Number

RoadMax RX2, 200W, 3000K, Type III, No Lens
RX2 200 E3 T3 G0

Test Number

Scaled from RX2-140E3T3G0-14703860.08A

Test Date

3/22/2023

The results contained in this report pertain only to this IES file.

RoadMax RX2, 200W, 3000K, Type III, No Lens
RX2 200 E3 T3 G0

Input

Number of Lamps	1
Lumens per Lamp	N/A lm
Total Input Lumens	N/A lm
Input Watts	200 W

Output

Total Output Lumens	24150 lm
Efficiency	N/A %
Efficacy	120.75 lm/W


Luminous Dimensions

0° - 180° Size	1.06 ft
90° - 270° Size	1.31 ft
Height	0 ft

Roadway Summary.

Total Luminaire Optical Efficiency	N/A %
IESNA lateral classification	Type III
IESNA vertical classification	Short
Cutoff classification	Noncutoff
IESNA TM-15-11 BUG Rating	B3 U0 G3
Maximum Candela	11251.1 at 77.5° horizontal, 65° vertical.
Street side total	73.63 %
House side total	26.37 %

Candela Polar Plot




Zonal Lumen Summary

Zone	Lumens	% Fixture	Zone	Lumens	% Fixture
0° - 10°	586.39	2.43%	90° - 100°	0.00	0.00%
10° - 20°	1625.74	6.73%	100° - 110°	0.00	0.00%
20° - 30°	2421.02	10.02%	100° - 120°	0.00	0.00%
30° - 40°	2973.05	12.31%	120° - 130°	0.00	0.00%
40° - 50°	3410.11	14.12%	130° - 140°	0.00	0.00%
50° - 60°	4525.67	18.74%	140° - 150°	0.00	0.00%
60° - 70°	5065.01	20.97%	150° - 160°	0.00	0.00%
70° - 80°	2919.89	12.09%	160° - 170°	0.00	0.00%
80° - 90°	623.11	2.58%	170° - 180°	0.00	0.00%
0° - 90°	24150.00	100.00%	0° - 180°	24150.00	100.00%
0° - 75°	22368.16	92.62%	75° - 90°	1781.83	7.38%

Average Luminare Luminance [cd/m²]


	0.00°	45.00°	90.00°
0.00°	46517	46517	46517
45.00°	63336	62568	78059
55.00°	83264	82510	118710
65.00°	41003	189303	186633
75.00°	12103	107083	222750
85.00°	9694	31876	113256

Roadway Coefficients of Utilization




Mounting Heights	1	2	3	4	5	6	7	8	9	10
House Side CU	0.22	0.25	0.26	0.26	0.26	0.26	0.26	0.26	0.26	0.26
Street Side CU	0.49	0.68	0.72	0.73	0.73	0.73	0.73	0.73	0.73	0.73

IES TM-15-11 BUG Ratings



Peak Intensity



Iso-Illuminance Plot

